

# FS SPECTRA LUBE® RED

## PREMIUM EP/AW, LITHIUM COMPLEX, HEAVY-DUTY GREASE

FS Spectra Lube Red is a high-quality lithium complex lubricating grease formulated with an advanced extreme-pressure/anti-wear (EP/AW) package for use in extreme-pressure and high-temperature operating conditions. Its well-balanced additive-thickener structure provides superior protection against water, rust, and corrosion for prolonged equipment life. FS Spectra Lube Red features a high dropping point in excess of 500°F and exhibits superior corrosion resistance, load-carrying ability, and compatibility with other greases. It is smooth textured with a tacky consistency and features a red color.

FS Spectra Lube Red is a multipurpose product suitable for farming, mining, and construction industries. It is ideal for garages that perform maintenance on trucks and automobiles.

### APPLICATIONS

Long-haul truck and heavy-duty fleets for extended service intervals

Agricultural, automotive, and industrial chassis and wheel bearings

Roller bearings, wheel bearings (with disc and conventional brakes), universal joints, ball joints, kingpins, sliding surfaces, bucket pins, ball bearings, needle bearings, anti-friction bearings, and similar applications

Sliding applications

Bearings working under wet, moderate- to high-temperature, and heavily loaded conditions

### BENEFITS & FEATURES

Enhanced film strength with special anti-wear and extreme-pressure additive system.

Well-balanced corrosion protection and load-carrying capability for extended bearing life.

High-temperature dropping point.

Pumpability in wide temperature ranges.

High mechanical stability provides prolonged re-lubrication intervals such as for bearings that are continuously running under heavy loads and elevated temperatures (e.g., truck wheel bearings during long-distance hauling).

Carries NLGI's highest automotive chassis and wheel-bearing lubricant classification, GC-LB.

### GRADE AND PACKAGING

FS Spectra Lube Red is available in NLGI No. 2 and packaged in 400-lb drums, 120-lb kegs, 35-lb pails, and 14-oz tubes.

Also available in NLGI No. 1 and packaged in 120-lb kegs, 35-lb pails, and 14-oz tubes.



# SPECTRA LUBE™



View our full product line at [fssystem.com](http://fssystem.com)

# GREASE COMPATIBILITY CHART

I = Incompatible

C = Compatible

BC = Borderline Compatible

	Aluminum Complex	Barium	Calcium	Calcium 12-Hydroxy	Calcium Complex	Bentone (Clay)	Lithium	Lithium 12-Hydroxy	Lithium Complex	Polyurea	Sodium
Aluminum Complex		I	I	C	I	I	I	I	C	I	I
Barium	I		I	C	I	I	I	I	I	I	I
Calcium	I	I		C	I	C	C	BC	C	I	I
Calcium 12-Hydroxy	C	C	C		BC	C	C	C	C	I	I
Calcium Complex	I	I	I	BC		I	I	I	C	C	I
Bentone (Clay)	I	I	C	C	I		I	I	I	I	I
Lithium	I	I	C	C	I	I		C	C	I	I
Lithium 12-Hydroxy	I	I	BC	C	I	I	C		C	I	I
Lithium Complex	C	I	C	C	C	I	C	C		I	I
Polyurea	I	I	I	I	C	I	I	I	I		I
Sodium (Soda Base)	I	I	I	I	I	I	I	I	I	I	



[fssystem.com](http://fssystem.com)