

# FS Synthetic Multi Vehicle ATF

---

---

## Description

The unique formulation of FS Synthetic Multi Vehicle ATF combines synthetic base oil with a high-performance additive package to provide excellent performance in such critical areas as low-temperature flow, wear protection, frictional stability, and resistance to thermal breakdown. These outstanding features translate into significant operational benefits.

## Features and Benefits:

- Protects metal parts from corrosion
- Provides excellent oxidative stability under severe conditions
- Reduces sludge and varnish buildup
- Protects transmission gears and allows them to operate smoothly
- Maintains lubricity
- Flows well for cold startup
- Provides excellent shift feel with no shudder
- Prevents fluid breakdown at higher operating temperatures
- Long fluid life and long transmission life
- Compatible with common transmission seal materials

## Recommended Use:

- Ford MERCON, MERCON V, MERCON SP, MERCON LV
- GM DEXRON VI and earlier DEXRON ATFs including DEXRON II and DEXRON III
- Allison C-4
- Both new and older Chrysler applications
- Acceptable in, but not limited to: Audi, Honda, Mazda, Nissan, Toyota, VW, BMW, Mitsubishi, Hyundai, Kia, Mercedes-Benz, Volvo
- Do not use where Type F fluids are recommended
- Not recommended for CVT or DCT transmissions

## Product Availability:

12 x 1 qt.	Item #257209
5 Gal. Pail	Item #257208
55-gal. Drum	Item #257207
265-gal. Totes	Item #257206
Bulk	Item #257205

## Typical Properties:

Test / Description	Specification
Viscosity @ 100°C (cSt)	6.6
Viscosity @ 40°C (cSt)	34.5
Viscosity Index	150
Density (lb/gal)	7.08
CCS Viscosity (cP)	NA
Pour Point (°C)	-42
Pour Point (°F)	-44
Flash Point (°C)	220
Flash Point (°F)	428
Color	Red